



RLM

REMOTE SAFETY INFLATORS



G995DG



G997



G997DG

Features

These "**Safety Inflation Assemblies**" are designed to allow the tyre technician, to inflate and pressure check tyres while located at a safe distance away or to the side of the tyre /wheel assembly, out of the trajectory zone should a tyre failure occur.

All models have 6 metres of Japanese made: light weight, high flex - polyurethane air hose, with ultra smooth Teflon bore for super fast airflow, assembled with nut-clamp fittings for secure hose connection, and infield serviceability.

They also feature : Full flow butterfly stop valves, NITTO quick connect couplers, to allow for easy interchange between small bore or large bore clip on tyre chucks, fitted with matching NITTO air plugs.

Technical Specifications

- **G995DG** :- For truck and machinery tyres : Has 8mm PU hose with 63mm liquid filled dial gauge, rubber protector and small bore air chuck.
- **G997** :- OTR tyre inflator : Has 11mm PU hose, large bore check valve and large bore clip on air chuck.
(This robust unit was designed for rough handling or storage in service truck tool boxes)
- **G997DG** :- Same as G997 model, but with 63mm liquid filled dial gauge and rubber protector.

Spare / replacement parts readily available from RLM Brisbane warehouse.

Supplier of Tyre and Wheel Servicing Products

Telephone: (07) 3277 9311
Website: www.rlmdistributing.com.au

Template Sales Brochure G995 - G997 .doc R180517_10B44D9A.doc

Facsimile: (07) 3875 1664
ABN 74 010 764 155